



Model: LP633870		Min.Capacity 最低容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	1700	Overcharge Detection Voltage (V) / 过充保护电压 (V) Overdischarge Detection Voltage (V) / 过放保护电压 (V) Limited to Max loading current 仅用于最大的负载电流 peak value (A) 持续 (A) Customer required Max loading current 客户要求最大的负载电流 peak value (A) 持续 (A)
Battery pack specification (电池组规格)		Typical Capacity 典型容量 (mAh) (0.2C, 25±3°C) *Single cell capacity (单体电芯容量)	1800	
		Nominal Voltage 标称电压 (V)	3.7	
		Internal impedance 内阻 (≦) (mΩ, AC 1KHz)	200	
Ambient Conditions (环境温度)		Charge Temp. 充电温度 (°C)	0~45	Battery protection Related Value: (相关的电池保护值)
		Discharge Temp. 放电温度 (°C)	-20~60	
		Humidity (湿度)	65±20%	

If actual application loading current is bigger than EEMB suggested, please indicate. The application profile is important for an appropriate PCM design.
(如果实际应用的负载电流大于EEMB提供值, 请提出来, 实际的应用情况对PCM的设计至关重要)

Remark(备注):
1. No scratch, discoloration, discoloration and leakage on the appearance of the cell(电池表面无划痕、变形、污点及漏液等现象).
2. Rohs compliant(严格按照ROHS要求生产).

		Drawn:	Zlimer	Revise No.:	E4-2009
		Checked 1:	Jane	Projection:	
Title	LP633870-LD/	Checked 2:		Page:	1/1
File NO.	A09519	Approved:		Scale:	1.1 : 1
		Draw Date:	2014/04/15	Unit:	mm