

Model Number : GNJA-12350Y



FEATURES :

Protections: short circuit/over voltage/Over temperature
IP66 design for indoor or outdoor installations
Cooling by free air convection
100% full load burn-in test
Suitable for LED lighting and moving sign applications
CE certified

OUTPUT :

Rated Current : 320mA-370ma
DC Voltage Range : 5 – 12VDC
Rated Power : 4.2W
Ripple & Noise (max.) : 150mVp-p
Voltage Tolerance : $\pm 5\%$

INPUT :

Voltage Range : 170 ~ 250VAC
Frequency Range: 47 ~ 63Hz
Efficiency(Typ.) : 76%
Inrush Current(max.) : COLD START 60A/230VAC
Leakage Current : 0.25mA / 240VAC

ENVIRONMENT :

Working Temperature : -25 ~ +40 \square
Working Humidity : 20 ~ 90% RH non-condensing
Storage Temp. , Humidity : -10 ~ +60 \square , 10 ~ 85% RH
TEMP. Coefficient : $\pm 0.03\%/ \square$ (0 ~ 50 \square)
Vibration : 10 ~ 500Hz, 2G 10min./1cycle, period for 60min. each along X, Y, Z axes

SAFETY :

Safety Standards : IEC 61347 -2-11 , IEC 61347 -1 , IEC 60529 , IP66 approved
Withstand Voltage : I/P-O/P: 3000KVAC
Isolation Resistance : I/P-O/P:100M Ohms/500VDC

OTHERS :

Dimension : 28*52 mm (D*H)
Packing : 60g ; 100pcs/6.0Kg/0.018CBM